

Selection and Ordering data		Order No.
Oval flange with female thread ½-14 NPT, max. working pressure 420 bar, flange connection to DIN EN 61518, form A		
Material P250GH, mat. No.: 1.0460		
X 2 CrNiMo 17 13 2, mat. No. 1.4404/316L		
F)	7MF9408-2CE	
F)	7MF9408-2CL	

Selection and Ordering data	Order code	Order No.
Further designs Please add "-Z" to Order No. and specify Order code.		
Accessory set to DIN¹⁾ 2x screws M10x40 to DIN EN ISO 4762; chromized steel 2x washers Ø 10.5 mm to DIN 125; 1x O-ring to DIN 3771, 20 x 2.65 - S - FPM90, max. permissible 420 bar, 120 °C ²⁾	E13	F) 7MF9408-6AA
	E16	F) 7MF9408-6BA
Accessory set to EN¹⁾ 2x screws 7/16-20 UNF x 1½ inch to ASME B 18.2.3; chromized steel 1x flat gasket made of PTFE, max. permissible 420 bar, 80 °C	E36	F) 7MF9408-5DA
	E34	F) 7MF9408-5CA

1) When ordering accessory set together with the oval flange, please use Order code; otherwise use Order No.

2) Flange connections with M10 screws only permissible up to PN 160!

F) Subject to export regulations AL: 91999, ECCN: N.